

The Monimax 5300CE offers powerful financial-transaction support. This high-volume ATM solution has a large cash capacity that gives customers reliable 24/7 access.

Features

TCP/IP with SSL Support

Monimax 5300CE includes built-in TCP/IP with Secure Socket Layers (SSL) for extra security while connected to the Internet. This new connectivity feature provides a direct connection without additional boxes, adaptors or converters. The result? A more efficient product that saves both time and money.

Capacity from 1,000 to 8,000 Notes

Customize a dispenser profile based on the volume of transactions at each Monimax 5300CE site. This scalable ATM is an ideal solution for multiple locations with various dispenser needs. Configuration can include up to three optional 2,000-note cassettes for a maximum of 8,000 notes.

Sophisticated Design

Featuring an easy-to-use 15" LCD display, bright lead-through indicator and an ergonomic design, the Monimax 5300CE is a smart choice for its small size and powerful functions.

Superior quality, security and value.

Only with Nautilus Hyosung.

Now offering the most complete line of financial and retail ATMs.



Experience a totally new ATM with Monimax 5300CE.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX 5300CE

System Control

- Intel® Xscale® processor
- Microsoft® Windows CE® platform

Communication

- TCP/IP (SSL configurable)

Optional

- Dial-up, Wireless

Customer Display

- 15" TFT LCD

Optional

- Privacy filter

Input Type

- 4 x 2 function keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Optional

- Touch screen

Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2 compliant

Cash Dispensing

- 2,000-note cassette
- Up to three cassettes (6,000 notes)

Printers

- 3.1" graphical thermal receipt printer
- 3,500 transactions
- Electronic journal

Security

- UL291 business hour safe
- Mechanical combination lock

Optional

- UL291 Level 1 safe
- Electronic safe lock
- KABA Mas Cenccon safe lock
- Security camera

Miscellaneous

- Lead-through indicator

Power Supply

- AC 110–240V, 50–60 Hz

Operating Environment

- Temperature: 28°F–104°F
- Humidity: 25%–85%

Dimension and Weight

- Height: 54.4" (1,381.9 mm)
- Width: 18.1" (460 mm)
- Depth: 25.4" (644 mm)
- Weight: 617 lbs (280 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



3.1" graphic thermal receipt printer

Key pad light

PCI EPP



Security camera (optional)

15" color customer display

- Optional sunlight viewable
- Optional touch screen

4 x 2 function keys

Lead thru indicator

Card reader

Cash dispenser

Nautilus
HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.